

## The NEMO configurations

---

### Table of Content

<b>The NEMO configurations</b>	<b>1</b>
<b>1. Description</b>	<b>2</b>
<b>2. Technical details</b>	<b>2</b>
2.1. The configuration on mod.def	2
2.2. Setting up pre-built NEMO configurations	2
2.2.1. Installation and Compiling	2
2.2.2. Creating the job	3
2.3. Running the model	3
2.3.1. Input files: atmospheric forcings, initial states, namelists	3
2.2.4. Submit the job	3
2.3. Performances	4

Person in charge: Christian Ethé

## 1. Description

The NEMO configuration described here is an ocean-sea ice configuration based on the version 3.6 stable of NEMO (Nucleus for European Models of the Ocean), which includes three major components: the ocean physics NEMO-OPA, the sea-ice dynamics and thermodynamics NEMO-LIM3 and the ocean biogeochemistry NEMO-PISCES. The available resolutions builded on the ORCA quasi-isotropic global tripolar grid are 2°, 1° and 1/4°. The 1° (eORCA1) and 1/4° (eORCA025) are extended to the south so as to better represent the contribution of Antarctic under-ice shelf seas to the Southern ocean freshwater cycle. Notice that the biogeochemical model PISCES can be run coupled online with the dynamics ( ORCA1-LIM3-PISCES for example ) or in a "stand-alone" ( ORCA2-LIM3-PISCES ). This NEMO configuration has been builded to be able to perform the OMIP6 experiments ( omip1 and omip2 protocol ) ; thus some specific sources code are available through the shaonemo repository.

To find out more about the model description and the reference configurations, go here: <http://www.nemo-ocean.eu/About-NEMO>. To use and extract NEMO, you first need to register and choose a login/passwd

## 2. Technical details

### 2.1. The configuration on mod.def

```
#--H- NEMO_v6_OMIP NEMOGCM for CMIP6 exercise
#--H- NEMO_v6_OMIP libIGCM trunk rev 1471
#--H- NEMO_v6_OMIP XIOS branch xios-2.5 rev 1550
#--M- NEMO_v6_OMIP Christian.Ethe@ipsl.fr
#--C- NEMO_v6_OMIP trunk/libIGCM                                1476 10 libIGCM .
#--C- NEMO_v6_OMIP branches/2015/nemo_v3_6_STABLE/NEMOGCM      9455 7 .
#--C- NEMO_v6_OMIP trunk/ORCA1_LIM3_PISCES                     275 17 .
#--C- NEMO_v6_OMIP trunk/eORCA025_LIM3                         275 17 .
#--C- NEMO_v6_OMIP trunk/eORCA025_LIM3_PISCES                  275 17 .
#--C- NEMO_v6_OMIP trunk/ORCA1_OFF_PISCES                      275 17 .
#--C- NEMO_v6_OMIP CONFIG/UNIFORM/v6/NEMO_v6                   4716 8 NEMO_v6 .
#--C- NEMO_v6_OMIP XIOS/branches/xios-2.5                      1550 12 XIOS .
```

### 2.2. Setting up pre-build NEMO configurations

#### 2.2.1. Installation and Compiling

```
mkdir $WORKDIR/NEMO_STD ; cd $WORKDIR/NEMO_STD
svn co http://forge.ipsl.jussieu.fr/igcmg/svn/modips1/trunk modips1
cd modips1/util

./model NEMO_v6_OMIP
```

Several built-in configurations are provided to evaluate the skills and performances of the model ( cd ..config/NEMO\_v6 ). They can be used as as first easy set-up and as template for setting up a new configuration :

- ORCA2\_LIM3\_PISCES : the fully coupled global ocean on 2° horizontal grid and 31 vertical levels, with 10 levels in the top 100m  
gmake ORCA2LIM3PISCES
- ORCA2\_OFF\_PISCES : stand-alone PISCES biogeochemical model on ORCA2 - dynamical fields are pre-calculated and read with specific time frequency  
gmake ORCA2OFFPISCES
- ORCA1\_LIM3\_PISCES : the fully coupled global ocean on 1° horizontal grid, extended to the south and 75 vertical levels ( from 1-m at the surface to 10-m at 100-m depth, and reaches 200-m at the bottom)

```
gmake ORCA1LIM3PISCES
```

- ORCA1\_LIM3\_PISCES\_CMIP6 : the ORCA1\_LIM3\_PISCES but to run the OMIP6 experiments

```
gmake ORCA1LIM3PISCES
```

- ORCA1\_OFF\_PISCES : stand-alone PISCES biogeochemical model on ORCA1

```
gmake ORCAOFFPISCES
```

- ORCA025\_LIM3 : the global ocean on 1/4° horizontal grid, without the PISCES model

```
gmake ORCA025LIM3
```

- ORCA025\_LIM3\_PISCES : the fully coupled global ocean on 1/4° horizontal grid

```
gmake ORCA025LIM3PISCES
```

## 2.2.2. Creating the job

For example : To perform an interannual COREII atmospheric forcing using the buildd eORCA1\_LIM3\_PISCES

```
cd modips1/config/NEMO_v6
cp EXPERIMENTS/ORCA1_LIM3_PISCES/ia/config.card .
.../.../libIGCM/ins_job
```

## 2.3. Running the model

### 2.3.1. Input files: atmospheric forcings, initial states, namelists

The card files ( opa9.card for orca1\_lim and pisces.card for pisces) contain the list of files needed to perform the simulation.  
These files are described here: [https://forge.ipsl.jussieu.fr/lqcmg\\_doc/wiki/DocModelAnemo](https://forge.ipsl.jussieu.fr/lqcmg_doc/wiki/DocModelAnemo)

```
## # The run ### This example is a 62 years CORE2 forcing interannual run of ORCA1_LIM3_PISCES split in 1-year jobs.
```

```
JobName=eOR1L3P-IA-CORE
#----- Short Name of Experiment
ExperimentName=ORCAlia
#----- DEVT TEST PROD
SpaceName=DEVT
LongName="ORCA1_LIM3_PISCES NEMO configuration"
TagName=ORCA1_LIM3_PISCES
#D- Choice of experiment in EXPERIMENTS directory
ExpType=ORCA1_LIM3_PISCES/ia
=====
#-- leap, noleap, 360d
CalendarType=noleap
#-- Begin and end of Job
#-- "YYYY-MM-DD"
DateBegin=1948-01-01
DateEnd=2009-12-31
=====
#-- 1Y, 1M, 5D, 1D
PeriodLength=1Y
```

## 2.2.4. Submit the job

```
on jean-zay : sbatch Job_eOR1L3P-IA-CORE
on irene : ccc_msub Job_eOR1L3P-IA-CORE
```

## 2.3. Performances

The performances of the eORCA1\_LIM3\_PISCES configuration can be find here: <http://forge.ipsl.jussieu.fr/igcmg/wiki/PerformancesIPSLCM6>